


Accessories - Instrument Quality Pressure Gauges

Pressures to 80,000 psi (5116 bar)

Gauges - Pressure gauges are offered for use in low, medium and high pressure systems. Instrument quality gauges are available with pressure to 80,000 psi (5115.7 bar).

Materials and Features

- Accuracy within $\pm 0.5\%$ of full scale range.
- Plastic dial cover/solid front aluminum alloy case.
- Blow-out back panel for pressure relief in the event of Bourdon tube failure.
- 316 Stainless steel Bourdon tubes**
- Precision stainless steel movement for accuracy and resistance to atmospheric corrosion.
- Pointer zero adjustment located on front of gauge behind dial cover for convenience
- Gauges are commercially cleaned when shipped.
- Gauges available oxygen cleaned upon request.
- Gauges glycerin filled upon request.
- Gauges available with dual scale face plates.



Instrument quality gauges

- **Flush panel mounting** - Interchangeable dial cover retaining rings are stocked to permit flush panel mounting of any instrument quality gauge. These will be furnished at an additional charge when specified - add "PM" to order number.
- **Optional electrical contact face** - Available for all instrument quality gauges. With adjustable low and high electrical contacts, this option permits gauges to provide pressure control for automatic or remote operation, or for fail-safe set points.

**Bourdon tube material for 0-30,000 psi (0-2068 bar) gauge is K Monel. Bourdon tube material for 0-50,000 psi (0-3447 bar) and 0-80,000 psi (0-5116 bar) gauge is Inconel 718.



Note: Gauge connections are 1/4" (F250C) coned-and-threaded connection. Furnished with collar and gland.


Calibrated in psi Only

Catalog Number	Pressure Range psi (bar)	Minor Interval Value psi (bar)	Dial Diameter inches (mm)
P-0499-CG	0-1,000 (0-69)	10 (.69)	4 1/2 (114.3)
P-0479-CG	0-1,500 (0-103)	10 (.69)	4 1/2 (114.3)
P-0480-CG	0-3,000 (0-207)	20 (1.38)	4 1/2 (114.3)
P-0481-CG	0-5,000 (0-345)	50 (3.44)	4 1/2 (114.3)
P-0482-CG	0-10,000 (0-690)	100 (6.89)	4 1/2 (114.3)
P-0483-CG	0-15,000 (0-1034)	100 (6.89)	4 1/2 (114.3)
P-0487-CG	0-20,000 (0-1379)	200 (13.79)	4 1/2 (114.3)
P-0488-CG**	0-30,000 (0-2068)	200 (13.79)	6 (152.4)
P-0489-CG**	0-50,000 (0-3447)	500 (34.47)	6 (152.4)
P-0490-CG**	0-80,000 (0-5116)	1,000 (68.94)	6 (152.4)

Optional Electrical Contact Face

Catalog Number	Fits Gauge Dial Diameter inches - (mm)
P-0713	4 1/2 (114.3)
P-0714	6 (152.4)

** Bourdon tube material for 0-30,000 psi (0-2068 bar) gauge is K Monel. Bourdon tube material for 0-50,000 psi (0-3447 bar) and 0-80,000 psi (0-5116 bar) gauge is Inconel 718.



Gauge Size inches - (mm)	"A" cutout inches - (mm)	"B" inches - (mm)	"C" inches - (mm)
4 1/2" (114.3)	4.937 (125.39)	5.375 (136.52)	.281 (7.14)
6" (152.4)	6.437 (163.49)	7.0 (177.80)	.281 (7.14)